Unit no. MP-523

IKM Testing AS

DIAPHRAGM PUMP 2" ATEX

Dimensions

Length(mm).....: 700 Width(mm).....: 600 Height(mm).....: 800
Weight (kg).....: 120
Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

Construction year

Built.....: 2020

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: EX / Atex, CE, Norsok, Zone 1

Type

Fabricator.....: Depa
Model.....: DB50BSA-ZHT
Serial no.....: Pump: 789371-3 Booster: 20032618

Flow / Pressure / Volume

Q-max (l/min).....: 300
P-max (bar).....: 16 P-max (PSI).....: 232

Connections

Inlet connection.....: 2" Camlock Male
Outlet connection.....: 2" Camlock Female
Air connection.....: 1" offshore claw coupling
Air supply (P@Q).....: Max 6,3 bar

Additional information

Equipment / Functions.....: Max. solid size (mm) 8
Max suction, dry : 6m

Pressure regulator on air supply to regulate flow / pressure.
Bonding cable with clamp and documentation tube.
Pump house material in cast stainless steel.
Enter medium, due to choice of gaskets.
Frame and wet parts, 316SS