



SUBMERSIBLE PUMP

Dimensions

Length(mm).....: 360 Width(mm).....: 360 Height(mm).....: 850
 Weight (kg).....: 90
 Lifting/ Transportation.....: Lifted by hook / handle grip

Construction year

Built.....: 2004

Area of use / certification

Onshore/offshore.....: Offshore

Type

Fabricator.....: ITT Flygt
 Model.....: 2125
 Serial no.....: 181-0430042

Flow / Pressure / Volume

Hz v Q-max measure.....: 60 Q-max (l/min).....: 1176
 Hz v P-max measure.....: 60 P-max (bar).....: 7.3

Connections

Inlet connection.....: Suction through pump casing
 Outlet connection.....: 1 ea 2" Camlock Female

Power supply

Fuse (A).....: 32
 El.Power1.....: 400 V (Hz).....: 50 (kW).....: 9,7 (A).....: 12,5
 El.Power2.....: 440-480 V (Hz).....: 60 (kW).....: 9,7 (A).....:
 Starter.....: CEAG GHG 635 1101 R0112
 12,5-16,0A

Additional information

Equipment / Functions.....: Delivered with a ca35 m supplycable and ca 45 m cable from enclosure to pump.
 Max pre-connected protection : 100 A/60 (ICS) @ 400V 100A/25KA(ICS) @ 500V